

8R/8RT/8RX TRACTORS

230-410 Engine Horsepower



JOHN DEERE



8R/8RT/8RX TRACTORS

TAKE THE NEXT LEAP FORWARD

At John Deere, we've cultivated more than 100 years of tractor expertise in the pursuit of progress for producers of all kinds. And it's all led to this – the newly redesigned 8 Series Tractors now available in three configurations – wheels, two-tracks and the game-changing four-track 8RX with exceptional traction and flotation. All with the most spacious and comfortable cab we've ever offered.

With more power, durability and comfort than any generation of 8 Series before it and intelligently built to deliver the most integrated experience an operator can have, these are the tractors to lead us into the next 100 years. The next leap forward in brains, brawn and beauty in a 230 to 410 hp tractor. So if you're ready to take your operation forward, see your John Deere dealer today.





CONTENTS

Take the next leap forward	2-3
8R Tractors	4-5
8RX Tractors.....	6-7
8RT Tractors	8-9
Our most spacious cab	10-11
Own the day.....	12-13
Own the night.....	14-15
Cab view	16-17
Power and efficiency.....	18-19
Precision ag technology	20-21
Hitches, axles, hydraulics.....	22-23
Maintenance support	24-25
8R Tractors Specifications	26-27
8RT Tractors Specifications	28-29
8RX Tractors Specifications.....	30-31
Dealer support	32



8RX TRACTORS

The future's on the right track: 8RX Tractors

You're looking at a bold leap forward in the 8 Series: the game-changing 8RX Four-Track Tractors. The only fixed-frame four-track row-crop tractor on the market. With everything you like about the 8R Tractors and inspired by our innovative 9RX Tractors, the 8RX has four independent tracks and a 4-post cab suspension to give you exceptional flotation, traction and ride quality.

You'll experience outstanding pulling power and efficiency, thanks to the John Deere PowerTech™ 9.0L engine and e23™ PowerShift or Infinitely Variable Transmission (IVT™). We made comfort a top priority with a new larger cab and an easy-to-adjust seat with massaging option for a secure ride in tough terrain. Plus, put total machine control in your hand with CommandPRO™ (IVT only) and all the latest technology you expect from John Deere through our Gen 4 CommandCenter™.

Four models from 310 to 410 engine hp.
Find out more at JohnDeere.com/8R or JohnDeere.ca/8R.

Choose from four tread settings – 76", 80", 88", 120" (193, 203, 223.5, 305 cm) – on three track widths 18", 24" and 30" (40.6, 45.7, 61 and 76.2 cm) - to fit your crop and field conditions.





8RT TRACTORS

The next level of two-track tractors: The 8RT

The next leap forward in two-track tractors is here: the new 8RT Tractors. By adding 40 extra horsepower to our top model, the 8RT delivers the straight-line pulling power and the traction and flotation you need to handle your toughest jobs. Our two-track design reduces ground pressure up to 37 percent compared to wheel models, reducing soil compaction.

You've asked for straight-line pulling power and efficiency and higher transport speeds. The 8RT delivers with our John Deere PowerTech™ 9.0L engine and your choice of e23™ PowerShift or Infinitely Variable Transmission (IVT™). You've asked for greater operator comfort. The 8RT delivers with our most spacious cab, comfortable seat and our exclusive AirCushion™ Suspension and 4-post cab suspension. We know you need greater machine control in one hand, and our CommandPRO™ (IVT only) delivers.

Four models from 310 to 410 engine hp. Find out more at JohnDeere.com/8R or JohnDeere.ca/8R.



Tread spacing from 72"-160" (182.9 - 406.4 cm) on 16", 18", 24", 25" and 30" (38.1, 45.7, 61.0, 63.5 and 76.2 cm) track widths to fit your job.



Cab sweet cab

When the hours are long and the terrain is tough, there's no better place to be than our all-new cab. Your home away from home. Step inside our most spacious cab through the 24% wider doorway than before. Enjoy more space than our previous cab, complete with extra headroom, extra storage capacity, and extra USB ports. Choose from these options; amenities vary by package. Discover more details at JohnDeere.com/8R or JohnDeere.ca/8R.

SELECT	PREMIUM	ULTIMATE
<ul style="list-style-type: none"> ■ Cloth seat with mechanical controls and mechanical lumbar support; 8° left-hand and 40° right-hand swivel ■ AM/FM/WX radio with auxiliary and Bluetooth inputs; 4 speakers ■ Business-band ready ■ 4 USB ports and 12V outlet ■ Dual-tilt steering column 	<ul style="list-style-type: none"> ■ Cloth seat with electronic controls and pneumatic lumbar support; 25° left-hand and 40° right-hand swivel ■ 6.5-inch (16.5 cm) touchscreen radio, SiriusXM ready; 6 speakers with subwoofer ■ Business-band ready ■ 4 USB ports, 12V outlet ■ Dual-tilt steering column ■ Foot rests ■ Refrigerator ■ Right-hand accessory rail ■ 120V outlet 	<ul style="list-style-type: none"> ■ Leather seat with electronic controls, massage and pneumatic lumbar support; 25° left-hand and 40° right-hand swivel; heated and ventilated; adjustable bolsters ■ 6.5-inch (16.5 cm) touchscreen radio, SiriusXM ready; 6 speakers with subwoofer ■ Business-band ready ■ 4 USB ports, 12V outlet ■ Dual-tilt steering column ■ Foot rests ■ Refrigerator ■ Right-hand accessory rail ■ Carpeted floor mat ■ Leather-wrapped steering wheel ■ 120V outlet



Ultimate Comfort and Convenience package shown.

8R/8RT/8RX TRACTOR CAB

Own the day

Take a seat in the most comfortable chair in the industry. And get ready to log serious hours in comfort, style and peak productivity.

A higher backrest and adjustable side bolsters let you sit comfortably within the seat. Massaging feature helps keep you alert when you're spending long hours in the cab. And since the seat is heated and ventilated, you'll stay warm or cool depending on the season. (Available in Ultimate Comfort & Convenience Package only)





1650⁰
8.0⁰
8.0⁰

JOHN DEERE

Default Tractor Run Page

04:32

100	36%	0	8.0 MPH	8.0 MPH	5.0	32.9 h	2100	126	1.4	1000	45.93	14.3
Country A												

Own the night

There's no better feeling than knowing you've put in a hard day's work. After all, this is no 9-to-5 job. When you've got a job to do, you keep going even when day turns into night.

Take charge of your night when the daytime hours aren't enough. Our new lighting packages are a bold leap forward, shedding new light on nighttime productivity. With two times more LED lighting than before, you'll get twice the light when compared to Halogen bulbs for a brighter, 360-degree illumination of the field around you. (Available in Ultimate Visibility Package). Choose from three Visibility Packages to help you make the most of your time, no matter the time; amenities vary by package.



SELECT	PREMIUM	ULTIMATE
<ul style="list-style-type: none"> ■ 18 Halogen work lights ■ Mechanical exterior mirrors ■ Front window sunshade ■ Front and rear window wipers ■ Camera ready 	<ul style="list-style-type: none"> ■ 18 LED work lights ■ Electronic, heated exterior mirrors ■ Front, right-hand, and rear window sunshades ■ Front, right-hand, and rear window wipers ■ Camera ready 	<ul style="list-style-type: none"> ■ 22 LED work lights, 8 LED convenience lights ■ Electric, heated, power telescoping exterior mirrors ■ Front, right-hand, and rear window sunshades ■ Front, right-hand, and rear window wipers ■ Front and rear integrated cameras



Ultimate Visibility package shown.

8R/8RT/8RX TRACTOR CAB

Enjoy the view

The view is amazing from any angle. Look at implements behind you with ease, thanks to three times more swivel to the left. Pneumatic lumbar support and electronic controls let you make adjustments with ease.



Shift into high gear

The John Deere PowerTech™ 9.0L engine and choice of transmissions deliver straight-line pulling power and efficiency while assuring excellent total fluid economy. Get uncompromised performance up to 410 engine horsepower, even higher through Intelligent Power Management. That's the most horsepower we've put in a row-crop tractor.

Power of choice in transmissions. Choose from e23™ PowerShift with Efficiency Manager™ with 23 forward gears evenly spaced 15% apart to fit your different operating conditions and implements. Or the Infinitely Variable Transmission (IVT™) that lets you move smoothly from 0 to 26 or 31 mph (40 or 50 km/h) — and any speed in between, including creeper speeds as low as 164 feet (50 m) per hour with a single lever. Or the 16-Speed PowerShift transmission for simple, reliable mechanical power.

New CommandPRO™ (IVT only) delivers seamless control of your tractor and implements all in the palm of your hand.





8R/8RT/8RX TRACTOR PRECISION AG TECHNOLOGY

Link up to the latest technology



It's easier than ever to have a connected machine. All new 8 Series tractors come standard with JDLink™ and five years of connected service* and capabilities, enabling you to easily benefit from technology-enabled machines.

By connecting through JDLink, you can wirelessly share information and plans with those who help you farm to make even better decisions. View reported work completed timely with Data Sync. Stay running in the field with help from your dealer using John Deere Connected Support™ and Remote Display Access. Keep track of your operation anytime and from anywhere from a desktop computer or a mobile device with John Deere Operations Center and MyOperations™ mobile app.

The primary user interface with the 8 Series Tractors is the Generation 4 CommandCenter™ Display for added productivity while boosting your confidence to make every pass more efficient.

Get started faster with more precision, less calibration and faster pull-in time with the integrated StarFire™ 6000 Receiver and SF3 signal. Precision Ag is built-in the tractor with AutoTrac™, Documentation, and Data Sync unlocked and ready for use. Find out more about all our latest technology including John Deere Operations Center at JohnDeere.com/8R or JohnDeere.ca/8R.



*Activation/subscription required. Some additional accessories and/or components may be required. JDLink requires a cellular connection to transfer information from machine to JDLink website. Consult your John Deere Dealer for coverage availability. Gen 4 Activations are machine specific activations that remain with the tractor. Free subscription to JDLink expires five years from date of purchase of qualifying 8R/8RT/8RX Tractor. This subscription will not be automatically renewed. To continue your subscription, you must actively renew and subscription fees shall apply.

8R/8RT/8RX TRACTOR HITCHES, AXLES, HYDRAULICS

The power-driven support you need

From pulling heavy tillage implements to large precision planters to side-dressing crops with minimal soil impact, the new 8R, 8RT and 8RX Tractors deliver more horsepower choices and greater operator comfort than before. With advanced steering technology, suspension systems and a 31-mph (50 km/h) transport option, these tractors are also right at home on the road.





You can handle some of the largest mounted implements in the industry including large planters.

8R, 8RT and 8RX tractors can be equipped with rear hitch options to handle up to 20,000 lbs. (9072 kg)

All 8 Series tractors have PTO options to suit many operations.

Optional dual hydraulic pumps with 84 GPM capacity on 8R and 8RX drive large hydraulic motors even at reduced engine speeds, giving you the power to run large planters and high demand hydraulic implements.

The connected support you need

When you're running, you don't want anything to slow you down. Your 8R/8RT/8RX Tractor comes with five years of JDLink™ connected service.* Once activated, your John Deere dealer can offer John Deere Connected Support services such as Remote Display Access and Service ADVISOR™ Remote, allowing your dealer to “dial in” to your tractor's diagnostic data and assess trouble codes to help you avoid downtime.

Protect your investment with a PowerGard™ Plan. The John Deere PowerGard Protection Plan lets you purchase extended coverage and powertrain warranty coverage for up to an additional three years or 3,000 hours over the normal warranty period. You get flexible coverage, low deductibles and peace of mind. Ask your dealer for details or go to www.powergard.com.

* Free subscription to JDLink expires five years from date of purchase of qualifying 8R/8RT/8RX Tractor. This subscription will not be automatically renewed. To continue your subscription, you must actively renew and subscription fees shall apply. For additional details, see footnote on page 21.

PowerGard Protection Plan extended warranty covers failures due to defective materials or original workmanship of covered components. Customers have a choice between either the Limited (engine & powertrain) coverage form or the Comprehensive (full-machine) coverage form. See your dealer or JohnDeere.com/PowerGard or JohnDeere.ca/PowerGard for details.





SPECIFICATIONS 8R TRACTORS

	8R 230	8R 250	8R 280	8R 310	8R 340	8R 370	8R 410
POWER							
Rated PTO power (hp SAE) at rated engine speed†	182 hp (135 kW)	200 hp (149 kW)	228 hp (170 kW)	257 hp (191 kW)	284 hp (211 kW)	310 hp (231 kW)	310 hp (231 kW)
Rated engine power PS (hp ISO) at rated engine speed (ECE-R120)*	230 hp (169 kW)	250 hp (184 kW)	280 hp (206 kW)	310 hp (228 kW)	340 hp (250 kW)	370 hp (272 kW)	410 hp (302 kW)
Max engine power PS (hp ISO) at max engine power speed (ECE-R120)*	253 hp (186 kW)	275 hp (202 kW)	308 hp (227 kW)	341 hp (251 kW)	374 hp (275 kW)	407 hp (299 kW)	443 hp (326 kW)
Intelligent Power Management* (Available)	35 additional engine horsepower PS (hp ISO) at 2,100 rpm (rated speed)						
PTO torque rise	40%						
PTO power bulge							8%
ENGINE							
Manufacturer (US EPA Final Tier 4)	John Deere PowerTech™ PVS 9.0L					John Deere PowerTech™ PSS 9.0L	
Rated speed				2,100 rpm			
Aspiration	Single turbocharger, variable geometry turbo					Dual turbochargers, variable geometry turbo with fixed geometry turbo in series	
Filter, engine air	Dual stage						
Displacement	549 cu in (9.0L)						
Bore and stroke	4.66 in (118.4 mm) x 5.35 in (136 mm)						
Compression ratio	16.0:1						
Lubrication	Full-pressure, full-flow filtration with bypass						
Filter, oil	Replaceable cartridge style oil filter						
FUEL SYSTEM							
Electronically controlled, high-pressure common rail with electric fuel transfer pump (self priming)							
Filter system	Two stage with water separator and service indicator light						
Filter, primary	10 micron spin on element w/water indication sensor and drain						
Filter, secondary	2 micron spin-on element						
Required fuel type	Ultra low sulfur diesel (B20 diesel compatible)						
TRANSMISSIONS							
16-speed PowerShift; 16F, 5R** with APS (Auto Power Shift)	Available (Forward: 42 km/h @ 2050 erpm, with group 49 tires, 42 km/h @ 2160 erpm, with group 48 tires, 40.8 km/h @ 2210 erpm, with group 47 tires Reverse: 30 km/h)***				NA		
e23 PowerShift 40K, 26 mph (40 km/h)	Standard (Forward: 42 km/h @ 1410 ECO erpm, with group 49 tires, 42 km/h @ 1480 ECO erpm, with group 48 tires, 42 km/h @ 1560 ECO rpm with group 47 tires Reverse: 30 km/h)**						
e23 PowerShift 50K, 31 mph (50 km/h)	Available (Forward: 50 km/h @ 1670 ECO erpm, with group 49 tires, 50 km/h @ 1770 ECO erpm, with group 48 tires, 50 km/h @ 1860 ECO rpm with group 47 tires Reverse: 30 km/h)**						
John Deere IVT™, 26 mph (40 km/h)	Available (Forward: 0.05 - 42 km/h, 42 km/h @ 1360 ECO erpm, with group 49 tires, 42 km/h @ 1430 ECO erpm, with group 48 tires, 42 km/h @ 1510 ECO rpm with group 47 tires Reverse: 0.05 - 21 km/h)**					NA	
John Deere Infinitely Variable Transmission, 31 mph (50 km/h)	Available (Forward: 0.05 - 50 km/h, 50 km/h @ 1630 ECO erpm, with group 49 tires, 50 km/h @ 1710 ECO erpm, with group 48 tires, 50 km/h @ 1810 ECO rpm with group 47 tires Reverse: 0.05 - 21 km/h)**					NA	
ELECTRICAL SYSTEM							
Two batteries in parallel							
Alternator/Battery	Standard: 250 amps / 12 volt, Available: 330 amps / 12 volt						
Total cold cranking amps	1850 (2-925 CCA grp 31 batteries)						
REAR AXLE FINAL DRIVES							
Description	Inboard planetary three pinion						
REAR AXLES							
110 x 3012 mm diameter (4.33 x 118.5 in), single taper hub	Standard					NA	
110 x 3012 mm diameter (4.33 x 118.5 in), dual taper hub	Available					NA	
120 x 3012 mm diameter (4.72 x 118.5 in), dual taper hub	Available			Standard		NA	
120 x 2550 mm diameter (4.72 x 100.4 in), double flat axle with single taper hub				Available			
120 x 3012 mm diameter (4.72 x 118.5 in), double flat axle with single taper hub				Available			Standard
REAR WHEEL EQUIPMENT							
Description	Group 47/48/49 tires available as singles/duals/triples						
FRONT AXLES							
1300 Series MFWD - tread range 60 to 88 in (1524 to 2235 mm) 5 step drop	Standard					NA	
1500 Series MFWD - tread range 60 to 144 in (1524 to 3657 mm) 5 step drop				Available w/ or w/o duals			
ILS - tread range 60 to 144 in (1524 to 3657 mm) 5 or 6 step drop	Available w/ or w/o duals					Standard w/ or w/o duals	
ILS/1500 3m tread spacing available	Field installed: 3 meter tread spacing available with front ballast limitations (no duals allowed)						
ILS - suspension travel	± 4.92 in (125 mm) at tread centerline for 5 step ratio axle at 1880 mm tread						
ILS with front brakes, available with 40K, available with 50K	Available w/ or w/o duals						
DIFFERENTIAL LOCK - FRONT AXLE							
1300 Series MFWD	Limited Slip					NA	
1500 Series MFWD	Full-locking electrohydraulic (actuated at same time as rear diff-lock)						
ILS	Full-locking electrohydraulic (actuated at same time as rear diff-lock)						
DIFFERENTIAL LOCK - REAR AXLE							
Full-Locking electrohydraulic	Standard						
HYDRAULIC SYSTEM							
Closed-center, pressure/flow compensated system with load sensing							
Rear selective control valves with 1/2 in ISO couplers	Standard: 4; Available: 5 - 6						
Rear selective control valves with 3/4 in and 1/2 in ISO couplers	Available: 5 (SCV 1: 3/4 in coupler, SCV 2-5: 1/2 in couplers)						
Main pump, axial piston (displacement)	Standard: 85cc, Available: dual pump (85cc plus 35cc)						
Maximum pressure	2,958 psi (20,400 ± 300 kPa)						
Rated flow, 85cc pump	60 gpm (227 lpm)						
Rated flow, dual pump 85cc plus 35cc	84 gpm (318 lpm)						
Available flow at a single rear SCV	35 gpm (132 lpm) 1/2 in coupler, 42 gpm (159 lpm) 3/4 in coupler						

Specifications and design subject to change without notice.
Pre-production models shown.

* John Deere Standard RES10080, SAE Standards J1995.

** Base tractor configuration on level ground, with specified tires groups above at mfg recommendation for tire pressure. erpm, are load dependent.

† PTO power for IVT models. Does not include available equipment losses.

Nominal data is metric. Standard data is converted from metric data. Use metric for all calculations.

	8R 230	8R 250	8R 280	8R 310	8R 340	8R 370	8R 410
3-POINT HITCH - REAR	(lift capacity per OECD: 24 inch / 610 mm behind the coupler) Electrohydraulic sensing						
Category 3/3N w/ Quick-Coupler - all axle diameters	Standard: 15,200 lb (6895 kg)			NA			
Category 3/3N w/ Quick-Coupler - 120 mm axle	Available: 18,500 lb (8391 kg)			NA			
Category 4N/3 w/ Quick-Coupler - all axle diameters				Available: 15,200 lb (6893 kg)			
Category 4N/3 w/ Quick-Coupler - 120 mm axle	Available: 20,000 lb (9072 kg)			Standard: 20,000 lb (9072 kg)			
REAR POWER TAKE OFF (PTO)	Independent, electrohydraulic switched via oil-cooled multi-disc clutch						
1-3/4 in, 20-spline, 1,000-rpm				Standard			
1-3/4 in, 20-spline, 1,000-rpm; capable of 1-3/8 in 540/1000 rpm	Available					NA	
1-3/4 in, 20-spline, 1,000-rpm / 1,000E RPM				Available			
PTO speed @ engine RPM	(1000 PTO rpm @ 2003 engine rpm, 1000 ECO PTO rpm @ 1596 engine rpm, and 540 PTO rpm @ 1817 engine rpm for 16 spd PST) (1000 PTO rpm @ 2000 engine rpm, 1000 ECO PTO @ 1594 engine rpm, and 540 PTO rpm @ 1814 engine rpm for IVT) (1000 PTO rpm @ 1995 engine rpm, 1000 ECO PTO @ 1590 engine rpm, and 540 PTO rpm @ 1810 engine rpm for e23 PST)						
3-POINT HITCH - FRONT	Category 3N ground engaging						
Standard lift capacity	11,464 lb (5200 kg)						
INTEGRATED TECHNOLOGY	Category 3N ground engaging						
Integrated AutoTrac™	Standard						
Modular Telematics Gateway (MTG)	Available with JDLink™ hardware, activations, and ethernet harnesses (availability dependent upon destination)						
Service Advisor™ Remote	Available with JDLink™ hardware and activations						
CAPACITIES	(lift capacity per OECD: 24 inch / 610 mm behind the coupler) Electrohydraulic sensing						
Fuel tank	192 gal (727 L)						
DEF tank	9.8 gal (37.2 L)						
WHEELBASE							
1300 Series MFWD / 1500 Series MFWD & ILS	121.3 in (3080 mm) / 120 in (3050 mm)			NA / 120.1 in (3050 mm)			
MFWD / ILS axle clearance	27 in (686 mm) / 23.2 in (590 mm)						
AVERAGE BASE WEIGHT							
IVT, ILS, 420/85R34 front tires, 480/80R50 rear tires, dual pumps, 6 SCVs, PTO, CAT4 hitch, HD drawbar, shipping fuel				27,800 lb (12600 kg)			
e23, ILS, 600/70R30 front tires, 710/70R42 rear tires, dual pumps, 6 SCVs, PTO, CAT4 hitch, HD drawbar, shipping fuel				28,000 lb (12700 kg)			
16spd, 1500 MFWD, 380/80R38 front tires, 480/80R50 rear tires, single pump, 4 SCVs, PTO, CAT3 hitch, std. drawbar, shipping fuel	25,200 lb (11400 kg)					NA	
e23, 1300 MFWD, 420/8R34 front tires, 480/80R50 rear tires, single pump, 4 SCVs, PTO, CAT3 hitch, std. drawbar, shipping fuel	25,800 lb (11700 kg)					NA	
CAB							
Cab glass area	70.61 sq ft (6.56 sq m)						
Cab volume	114.42 cu ft (3.24 cum)						



SPECIFICATIONS 8RT TRACTORS

	8RT 310	8RT 340	8RT 370	8RT 410
POWER				
Rated PTO power (hp SAE) at rated engine speed* †	246 hp (183 kW)	273 hp (203 kW)	300 hp (223 kW)	300 hp (223 kW)
Rated engine power PS (hp ISO) at rated engine speed (ECE-R120)*	310 hp (228 kW)	340 hp (250 kW)	370 hp (272 kW)	410 hp (302 kW)
Max engine power PS (hp ISO) at max engine power speed (ECE-R120)*	341 hp (251 kW)	374 hp (275 kW)	407 hp (299 kW)	443 hp (326 kW)
Intelligent Power Management* (Available)	35 additional engine horsepower PS (hp ISO) at 2,100 RPM (rated speed)			
PTO torque rise			40%	
PTO power bulge	10%			8%
ENGINE				
Manufacturer (US EPA Final Tier 4)	John Deere PowerTech™ PVS 9.0L		John Deere PowerTech™ PSS 9.0L	
Rated speed			2,100 rpm	
Aspiration	Single turbocharger, variable geometry turbo		Dual turbochargers, variable geometry turbo with fixed geometry turbo in series	
Filter, engine air			Dual stage	
Displacement			549 cu in (9.0L)	
Bore and stroke			4.66 in (118.4 mm) x 5.35 in (136 mm)	
Compression ratio			16.0:1	
Lubrication			Full-pressure, full-flow filtration with bypass	
Filter, oil			Replaceable cartridge style oil filter	
TRANSMISSIONS				
e23 PowerShift 40K, 26 mph (40 km/h) with Efficiency Manager™			Available: (Forward: 42 km/h @ 1600 ECO erpm; Reverse: 30 km/h)**	
Infinitely Variable Transmission (IVT™) 26 mph (40 km/h)	Standard: (Variable forward: 0.05 - 42 km/h, 42 km/h @ 1550 ECO erpm; Variable reverse: 0.05 - 21 km/h)**		NA	
REAR AXLES				
Tread spacing, standard			72 - 120 in (1829 - 3048 mm)	
Tread spacing, available			112 - 160 in (2845 - 4064 mm)	
Drive type			Friction	
Track width	16 in (406 mm), 18 in (457 mm), 24 in (609 mm), 25 in (635 mm), 30 in (762 mm)			
Drive wheel width			15 in (381 mm), 24 in (610 mm)	
Midroller width			15 in (381 mm), 24 in (610 mm)	
Midrollers			Polyurethane or rubber	
STEERING				
	Tilt & telescope steering with memory function			
Hydraulic power steering w/ electronic back-up pump	Ratio/turns lock-to-lock: 1.8, speed sensitivity adjustment			
HYDRAULIC SYSTEM				
	Closed-center, pressure/flow compensated system with load sensing			
Rear selective control valves with 1/2 in ISO couplers	Standard: 4; Available: 5 - 6			
Rear selective control valves with 3/4 in and 1/2 in ISO couplers	Available: 5 (SCV1: 3/4 in coupler, SCV2-5: 1/2 in couplers)			
Main pump, axial piston (displacement)	Single pump 85cc			
Maximum pressure	2,958 psi (20,400 ± 300 kPa)			
Rated flow, 85cc pump	60 gpm (227 lpm)			
Available flow at a single rear SCV	35 gpm (132 lpm) 1/2 in coupler, 42 gpm (159 lpm) 3/4 in coupler			
3-POINT HITCH - REAR Lift capacity per OECD: 24 inch / 610 mm behind the coupler				
	Electrohydraulic sensing			
Category 4N/3 with Quik-Coupler and sway blocks	Available: 15,200 lb (6894 kg)			
Category 4N/3 with Quik-Coupler and sway blocks	Standard: 20,000 lb (9072 kg)			
REAR POWER TAKE OFF (PTO)				
	Independent, electrohydraulic switched via oil-cooled multi disk clutch			
1-3/4 in (45 mm), 20-spline, 1,000-rpm	Standard			
PTO speed @ engine RPM	1000 PTO rpm @ 2000 engine rpm			
BRAKES				
Description	Power, disc			
CAPACITIES				
Fuel tank	202 gal (764 L)			
DEF tank	8.3 gal (31.3 L)			
WHEELBASE				
Description	97.5 in (2477 mm)			
AVERAGE BASE WEIGHT				
e23, 30in tracks, 5 SCVs, CAT4 hitch, HD drawbar, shipping fuel	36,500 lb (16600 kg)			
IVT, 18in tracks, 5 SCVs, CAT4 hitch, HD drawbar, shipping fuel	35,850 lb (16200 kg)			
e23, 25in tracks, 5 SCVs, CAT4 hitch, HD drawbar, shipping fuel	34,400 lb (15600 kg)			

Specifications and design subject to change without notice.

Pre-production models shown.

* John Deere Standard RES100B0, SAE Standards J1995.

** Base tractor configuration on level ground, with specified tires groups above at mfg recommendation for tire pressure. erpm, are load dependent.

† PTO power for IVT models. Does not include available equipment losses.

Nominal data is metric. Standard data is converted from metric data. Use metric for all calculations.





SPECIFICATIONS 8RX TRACTORS

	8RX 310	8RX 340	8RX 370	8RX 410
POWER				
Rated PTO power (hp SAE) at rated engine speed†	257 hp (191 kW)	284 hp (211 kW)	310 hp (231 kW)	310 hp (231 kW)
Rated engine power PS (hp ISO) at rated engine speed (ECE-R120)*	310 hp (228 kW)	340 hp (250 kW)	370 hp (272 kW)	410 hp (302 kW)
Max engine power PS (hp ISO) at max engine power speed (ECE-R120)*	341 hp (251 kW)	374 hp (275 kW)	407 hp (299 kW)	443 hp (326 kW)
Intelligent Power Management* (Available)	35 additional engine horsepower PS (hp ISO) at 2,100 RPM (rated speed)			
PTO torque rise			40%	
Engine power bulge*	10%			8%
ENGINE				
Manufacturer (US EPA Final Tier 4)	John Deere PowerTech™ PVS 9.0L		John Deere PowerTech™ PSS 9.0L	
Rated speed			2,100 rpm	
Aspiration	Single turbocharger, variable geometry turbo		Dual turbochargers, variable geometry turbo with fixed geometry turbo in series	
Filter, engine air			Dual stage	
Displacement			549 cu in (9.0L)	
Bore and stroke			4.66 in (118.4 mm) x 5.35 in (136 mm)	
Compression ratio			16.0:1	
Lubrication			Full-pressure, full-flow filtration with bypass	
Filter, oil			Replaceable cartridge style oil filter	
TRANSMISSIONS				
e23 PowerShift 40K, 26 mph (40 km/h) with Efficiency Manager™			Standard	
Infinitely Variable Transmission (IVT™) 26 mph (40 km/h)	Available		NA	
REAR AXLES				
Tread spacing	76 in (1930.4 mm), 80 in (2032 mm), 88 in (2235.2 mm), 120 in (3048 mm)		Flange axle	
Drive type			Positive	
Track width	18 in (457 mm), 24 in (610 mm), 30 in (762 mm)			
Midrollers			Polyurethane	
FRONT AXLE				
1700 Series MFWD - tread spacing	76 in (1930.4 mm), 80 in (2032 mm), 88 in (2235.2 mm), 120 in (3048 mm)			
Front undercarriage pivot	± 7° for 76 in (1930.4 mm), 80 in (2032 mm), 88 in (2235.2 mm), ± 10° for 120 in (3048 mm)			
Drive type			Positive	
Track width	18 in (457 mm), 24 in (610 mm)			
Midrollers			Polyurethane	
STEERING				
	Tilt & telescope steering with memory function			
Hydraulic power steering w/ electronic back-up pump			Standard	
DIFFERENTIAL LOCK				
	Tilt & telescope steering with memory function			
1700 Series MFWD			Full-locking electrohydraulic (actuated at same time as rear diff-lock)	
Rear axle			Full-locking electrohydraulic	
HYDRAULIC SYSTEM				
	Closed-center, pressure/flow compensated system with load sensing			
Rear selective control valves with 1/2 in ISO couplers			Standard: 4; Available: 5 - 6	
Rear selective control valves with 3/4 in and 1/2 in ISO couplers			Available: 5 (SCV 1: 3/4 in coupler, SCV 2-5: 1/2 in couplers)	
Main pump, axial piston (displacement)			Standard: 85cc, Available: dual pump (85cc plus 35cc)	
Maximum pressure			2,958 psi (20,400 ± 300 kPa)	
Rated flow, single pump 85cc			60 gpm (227 lpm)	
Rated flow, dual pump 85cc plus 35cc			84 gpm (318 lpm)	
Available flow at a single Rear SCV	35 gpm (132 lpm) 1/2 in couplers, 42 gpm (159 lpm) 3/4 in coupler			
3-POINT HITCH - REAR Lift capacity per OECD: 24 inch / 610 mm behind the coupler				
	Electrohydraulic sensing			
Category 4N/3 with Quik-Coupler and sway blocks			Available: 15,200 lb (6894 kg)	
Category 4N/3 with Quik-Coupler and sway blocks			Standard: 20,000 lb (9072 kg)	
REAR POWER TAKE OFF (PTO)				
	Independent, electrohydraulic switched via oil-cooled multi disk clutch			
1-3/4 in (45 mm), 20-spline, 1,000-rpm			Standard	
1-3/4 in, 20-spline, 1,000-rpm; capable of 1-3/8 in 540/1000 rpm	Available		NA	
1-3/4 in, 20-spline, 1,000-rpm / 1,000 RPM			Available	
PTO speed @ engine RPM	(1000 PTO rpm @ 2003 engine rpm, 1000 ECO PTO rpm @ 1596 engine rpm, and 540 PTO rpm @ 1817 engine rpm for 16 spd PST) (1000 PTO rpm @ 2000 engine rpm, 1000 ECO PTO @ 1594 engine rpm, and 540 PTO rpm @ 1814 engine rpm for IVT) (1000 PTO rpm @ 1995 engine rpm, 1000 ECO PTO @ 1590 engine rpm, and 540 PTO rpm @ 1810 engine rpm for e23 PST)			
BRAKES				
Description	Power, dual disc			
CAPACITIES				
Fuel tank	245 gal (927 L)			
DEF tank	9.8 gal (37.2 L)			
WHEELBASE				
MFWD	127.36 in (3235 mm)			
AVERAGE BASE WEIGHT				
e23, 24in front, 30in rear, 88in spacing, dual pumps, 5 SCVs, PTO, CAT4 hitch, HD drawbar, shipping fuel			41,600 lb (18900 kg)	
IVT, 18in front, 18in rear, 120in spacing, dual pumps, 5 SCVs, PTO, CAT4 hitch, HD drawbar, shipping fuel			43,000 lb (19500 kg)	
e23, 24in front, 24in rear, 120in spacing, dual pumps, 5 SCVs, PTO, CAT4 hitch, HD drawbar, shipping fuel			43,300 lb (19600 kg)	

Specifications and design subject to change without notice.
Pre-production models shown.

* John Deere Standard RES10080, SAE Standards J1995.

** Base tractor configuration on level ground, with specified tires groups above at mfg recommendation for tire pressure. erpm, are load dependent.

† PTO power for IVT models. Does not include available equipment losses.

Nominal data is metric. Standard data is converted from metric data. Use metric for all calculations.







Supported by one of the most responsive dealer networks in the business

Nobody cares more about keeping your equipment in solid working order than your John Deere dealer. With a complete inventory of genuine John Deere parts, highly trained service technicians, and a thorough understanding of your business, your John Deere dealer knows how to keep you and your equipment up and running.

A strong name in equipment, and a strong dealership network: get it all with John Deere.

This literature has been compiled for worldwide circulation. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specification and design of all products described in this literature without notice. Copyright 2020 Deere & Company.

